

# **TECHNICAL SPECIFICATIONS**

## FOOTWEAR STYLE 403, DUAL DENSITY POLYURETHANE INJECTED

Ultra-lightweight safety work shoe. With steel or composite toe cap.

This model is ergonomically designed, made with black full grain leather. It has a SicMesh<sup>®</sup> inner lining (textile and 100% breathable). The shoe is sewn with triple stitching and has padding on the upper part of the heel for extra comfort.

The boot has a composition leather counter, a bellows tongue (stitched-in tongue) to minimize penetration of fluids, and a polyester-based insole with SicTex<sup>®</sup> membrane (antibacterial and extremely breathable).

The outsole is made of dual-density elastomeric microcellular polyurethane, made of a polyurethane midsole with lower density (to increase cushioning) and an extremely flexible and lightweight outsole.

### MATERIAL SPECIFICATIONS

#### Protective toe cap:

Minimal residual height of toe cap is 19.5 mm, Steel or composite. If Steel, made with SAE 1050 Steel, hardened with electrostatic epoxy coating, resistant to corrosión, impact and compression.

Puncture resistant textile midsole, 100% metal free (1.100 N force)



ASTM 2412 UNE EN ISO 20344 NVC 39:2003 PDVSA EM 36-01/01

### OUTSOLE

Grade 1 Polyurethane outsole according to ASTM D3851, formulated to resist hydrocarbon fuels and lubricants. Anti-slip and doesn't scratch the floor.

#### **General Properties of the Outsole:**

- Tensile strength and elongation to breaking point (higher than 4.9 MPa and 300%)
- Tear strength (higher than 22.0 and 11.5 KN/m)
- Bending fatigue resistance: 150,000 cycles
- Abrasion resistance:
  - $\circ \leq$  300 mm3: E.T.M. PDVSA,  $\leq$  350 mm<sup>3</sup>: ISO 4649 standard

Test Standard	Specificatio
Test Standard	Specificat

ASTM 2412 UNE EN ISO 20344 NVC 39:2003 PDVSA EM 36-01/01

#### MANUFACTURED SHOE

#### **General Properties of manufactured shoe:**

Resistance of union of upper-sole: 800 N force
Test voltage of 14 kV for AC (alternating current) with leakage current less than or equal to 3 milli Ampere (mA). For DC (direct current) at 20 kV with leakage current not greater than 200 micro Ampere (μA).
Impact test on footwear: 12.5 mm minimal height.
Compression test: 19.5 mm minimal height.

Puncture resistance: 1.100 N force

Specification

ASTM 2412 UNE EN ISO 20344 NVC 39:2003 PDVSA EM 36-01/01

the second secon

"At Calzados Sicura, we develop and manufacture industrial safety and work shoes with the highest quality standards, complying with the requirements of our clients and any applicable standards, working with a valuable team focused on continually improving our Management System.." Política de la Calidad de Calzados Sicura, C.A.