

STYLE
207
>>>



DESCRIPTION

Safety footwear made of full-grain leather, black. Dual-density polyurethane outsole with anti-slip grooves. Direct injection to the upper.

SRB level.

Upper: black cowhide leather.

Lining: SicMesh®, 100% breathable and abrasion-resistant textile.

Removable insole: polyester-based with SicTex® membrane, breathable, antibacterial and extremely breathable fabric.

Outsole: double density polyurethane, with anti-slip grooves. Resistant to hydrocarbon fuels and lubricants.

Protective toe: steel or composite as required. Resistant to impact and compression.

Protective midsole (optional): textile anti-perforation insole, 100% metal free, resistant to 1,100 N of force.

RELEVANT ESSAYS

Impact and compression resistance of the toe cap and protective footwear (ASTM F2413, EN ISO 20345, Covenin 39): Steel or composite toe cap resistant to an energy of 200 ± 4 JI 100 ± 4 J.

Floor-shear bond strength: ≤ 4.0 N/mm force. (According to UNE EN ISO 20345).



WEIGHT:
950 gr / pair
approx. (Size 41)

SIZES:
35 to 50

CERTIFICATES:
ASTM F2413
UNE-EN ISO 20345



AC/DC Electrical Isolation:

| Standard | Specification | |
|------------|---------------|-------|
| | DC | AC |
| Covenin 39 | 20 kV | 14 kV |
| ASTM F2413 | | 18 kV |



Impact and compression resistance



Slip resistant outsole



Energy absorption of seat region



Fuel oil resistant sole



Fuel oil resistant sole



Natural Leather



SicTex®



SicMesh®