

# STYLE 683



## DESCRIPTION

High-top tubular type safety footwear, made with greased "Pull Up" oiled leather, brown. Dual-density polyurethane outsole with anti-slip grooves. SRB level. Direct injection to the upper.

**Upper:** "Pull-Up" oiled leather, brown.

**Lining:** SicMesh®, 100% breathable and abrasion-resistant textile.

**Removable insole:** polyester-based with SicTex® membrane, breathable, antibacterial and extremely breathable fabric.

**Outsole:** double density polyurethane, with anti-slip grooves. Resistant to hydrocarbon fuels and lubricants.

**Protective toe:** steel or composite as required. Resistant to impact and compression.

**Protective midsole (optional):** textile anti-perforation insole, 100% metal free, resistant to 1,100 N of force.

## RELEVANT ESSAYS

**Impact and compression resistance of the toe cap and protective footwear (ASTM F2413, EN ISO 20345, Covenin 39):** Steel or composite toe cap resistant to an energy of 200 ± 4 JI 100 ± 4 J.

**Floor-shear bond strength:** ≤ 4.0 N/mm force. (According to UNE EN ISO 20345).



**WEIGHT:**  
1.250 gr / pair  
approx. (Size 41)

**SIZES:**  
35 to 50

**CERTIFICATES:**  
ASTM F2413  
UNE-EN ISO 20345



Impact and compression resistance



Slip resistant outsole



Energy absorption of seat region



Fuel oil resistant sole



Fuel oil resistant sole



Natural Leather



SicTex®



SicMesh®

### AC/DC Electrical Isolation:

Standard	Specification	
	DC	AC
Covenin 39	30 kV	14 kV
ASTM F2413		18 kV